

HUBATS® Hubats Technology Co.,Ltd

Add: 2th Building, Dabu industrial Zone, Longhu town, Quanzhou, Fujian, China

Website: www.hubats.com Email: info@hubats.com Tel.: +86 595 22417374

Li-ion Cylindrical Battery

| Size | Model | Nominal Voltage (V) | Nominal Capacity (mAh) | Dimension | | Standard charge Current (mA) | Internal Resistance (mΩ) | Weight Approx(g) |
|---------|--------|---------------------|------------------------|-----------------|---------------|------------------------------|--------------------------|------------------|
| | | | | Diameter (mm±3) | Height (mm±3) | | | |
| ICR | 18650C | 3.7 | 2600 | 18 | 64.7 | 1300 | <65 | 46 |
| | 18650C | 3.7 | 2400 | 18 | 64.7 | 1200 | <65 | 45 |
| | 18650C | 3.7 | 2200 | 18 | 64.7 | 1100 | <65 | 43 |
| | 18500C | 3.7 | 1600 | 18 | 49.7 | 1600 | <65 | 34 |
| | 14280C | 3.7 | 320 | 13.9 | 28 | 160 | <100 | 10 |
| INR | 18650 | 3.7 | 2200 | 18 | 64.7 | 1100 | <65 | 43 |
| | 18650 | 3.7 | 2000 | 18 | 64.7 | 1000 | <65 | 41.5 |
| | 18650 | 3.7 | 1800 | 18 | 64.7 | 900 | <65 | 40.5 |
| | 18650 | 3.7 | 1500 | 18 | 64.7 | 800 | <65 | 40 |
| | 18500 | 3.7 | 1500 | 18 | 49.7 | 700 | <60 | 34 |
| | 18500 | 3.7 | 1400 | 18 | 49.7 | 700 | <60 | 34 |
| | 18500 | 3.7 | 1200 | 18 | 49.7 | 600 | <60 | 32.5 |
| | 16500 | 3.7 | 1200 | 16 | 50.2 | 600 | <55 | 26.5 |
| | 14650 | 3.7 | 1050 | 13.9 | 64.7 | 500 | <55 | 25.5 |
| | 14650 | 3.7 | 1000 | 13.9 | 64.7 | 500 | <55 | 25 |
| | 14500 | 3.7 | 800 | 13.9 | 50.2 | 400 | <50 | 18.5 |
| | 14500 | 3.7 | 700 | 13.9 | 50.2 | 375 | <50 | 18.5 |
| | 14430 | 3.7 | 650 | 13.9 | 43 | 325 | <65 | 16 |
| | 14430 | 3.7 | 550 | 13.9 | 43 | 275 | <65 | 16 |
| | 22650 | 3.7 | 3000 | 22 | 65.2 | 1500 | <35 | 70 |
| | 26650 | 3.7 | 4000 | 26.5 | 65.2 | 2000 | <55 | 88 |
| | 26650 | 3.7 | 4300 | 26 | 65.5 | 2100 | <55 | 90 |
| | 26500 | 3.7 | 3000 | 26.5 | 50.2 | 1500 | <55 | 64 |
| | 22430 | 3.7 | 2000 | 22 | 42.7 | 1000 | <40 | 42 |
| | | 26650MP | 3.7 | 4200 | 26.5 | 65.5 | 2100 | <12 |
| 26650HP | | 3.7 | 3400 | 26 | 65.5 | 1700 | <12 | 85 |
| 22650HP | | 3.7 | 2000 | 22 | 65.2 | 2000 | <15 | 56 |
| 22430HP | | 3.7 | 1300 | 23.5 | 43 | 650 | <18 | 41 |
| 18650HP | | 3.7 | 1500 | 18 | 64.7 | 1500 | <18 | 41 |
| 18650HP | | 3.7 | 1300 | 18 | 64.7 | 1300 | <21 | 37 |
| 18500HP | | 3.7 | 1100 | 18 | 49.7 | 1100 | <18 | 32 |
| 18350HP | | 3.7 | 700 | 18 | 35 | 700 | <30 | 21 |
| 16500HP | | 3.7 | 800 | 16.3 | 49.7 | 800 | <25 | 24 |
| 16340HP | | 3.7 | 600 | 16.8 | 34 | 600 | <40 | 16.5 |
| 14500HP | | 3.7 | 650 | 13.9 | 49.7 | 650 | <24 | 18 |

| | | | | | | | | |
|---------|---------|-----|------|------|------|------|------|------|
| INR(P) | 14280HP | 3.7 | 280 | 13.9 | 28 | 280 | <40 | 10.5 |
| | 18650MP | 3.7 | 2200 | 18 | 65 | 2200 | <18 | 44 |
| | 18650MP | 3.7 | 2000 | 18 | 65 | 2000 | <35 | 41 |
| | 18350MP | 3.7 | 850 | 18 | 35 | 850 | <70 | 21.5 |
| | 13450MP | 3.7 | 550 | 12.5 | 45 | 550 | <65 | 14.5 |
| | 13650MP | 3.7 | 800 | 12.5 | 65 | 800 | <50 | 16 |
| LiFePO4 | 26650 | 3.2 | 3000 | 26 | 65.5 | 3000 | <30 | 85 |
| | 18650 | 3.2 | 1500 | 18 | 64.7 | 1500 | <65 | 40 |
| | 18500 | 3.2 | 1100 | 18 | 49.7 | 1100 | <60 | 34 |
| | 14500 | 3.2 | 500 | 13.9 | 49.7 | 500 | <80 | 22 |
| | 14430 | 3.2 | 400 | 13.9 | 42.7 | 400 | <100 | 19 |

MP: 3-5C Discharge Rate; HP: 10C Discharge Rate