

HUBATS[®] Hubats Technology Co.,Ltd

Add: 2th Building, Dabu industrial Zone, Longhu ton, Quanzhou, Fujian, China

Website: www.hubats.com Email: info@hubats.com Tel.: +86 595 22417374

Li-Polymer battery

NO.	Model NO	Nominal Capacity (mAh)	Voltage (V)	Dimension			Approx weight (g)	Internal Impedance (mΩ)	Max Discharge Current		
				T ±0.2 mm	±0.5 mm	L ±1.0 mm			Continuous Discharge	Burst Discharge Current	Cut-off Voltage (V)
1	401220-60	60	3.7	4.0	12	20	1.3	≤500	1C	2C	2.75
2	501023-70	70	3.7	5	10	23	1.8	≤330	1C	2C	2.75
3	451321-75	75	3.7	4.5	13	22	1.9	≤300	1C	2C	2.75
4	10160-80	80	3.7	8.5	10	16	1.8	≤392	1C	2C	2.75
5	381225-80	80	3.7	4	12	25	1.9	≤400	1C	2C	2.75
6	581519-100	100	3.7	5.2	15	19	2.2	≤241	1C	2C	2.75
7	601520-100	100	3.7	5.8	15	20	2.5	≤225	1C	2C	2.75
8	401230-110	110	3.7	4	12	30	2.5	≤450	1C	2C	2.75
9	621520-120	120	3.7	5.8	15	20	2.5	≤225	1C	2C	2.75
10	551132-140	140	3.7	≤5.7	11	32		≤200	1C	2C	2.75
11	402025-150	150	3.7	4.0	20	25	3.2	≤215	1C	2C	2.75
12	601522-150	150	3.7	≤6.2	15	22		≤170	1C	2C	3.75
13	322027-160	160	3.7	3.4	20	27	3.4	≤180	1C	2C	2.75
14	402030-175	175	3.7	4	20	30	3.9	≤170	1C	2C	2.75
15	452030-200	200	3.7	4.5	20	30	4.8	≤160	1C	2C	2.75
16	401545-220	220	3.7	4	15	45	4.7	≤130	1C	2C	2.75
17	601730-220	220	3.7	6.0	17	30	4.9	≤165	1C	2C	2.75
18	581730-240	240	3.7	≤5.8	17	30		≤220	1C	2C	2.75
19	602025-240	240	3.7	6.0	20	25	4.9	≤150	1C	2C	2.75
20	401265-250	250	3.7	≤4.2	11	65		≤130	1C	2C	2.75
21	451543-260	260	3.7	4.5	15	43	5.3	≤120	1C	2C	2.75
22	502035-300	300	3.7	5	20	35	6.2	≤119	1C	2C	2.75
23	602425-300	300	3.7	≤6.0	24	25		≤120	1C	2C	2.75
24	502435-350	350	3.7	5.0	24	35	7.4	≤120	1C	2C	2.75
25	602530-380	380	3.7	≤6.0	25	30.5		≤110	1C	2C	2.75
26	752030-380	380	3.7	7.5	20	30	7.5	≤102	1C	2C	2.75
27	501271-390	390	3.7	≤5.3	11.5	71		≤80	1C	2C	2.75
28	552240-400	400	3.7	5	22	40	8.5	≤80	1C	2C	2.75
29	622530-400	400	3.7	≤6.2	25	30		≤110	1C	2C	2.75
30	651260-400	400	3.7	≤6.7	12	61		≤80	1C	2C	2.75
31	652035-400	400	3.7	6.3	20	35	7.8	≤98	1C	2C	2.75
32	752530-450	450	3.7	7.5	25	30	9.0	≤105	1C	2C	2.75
33	652240-500	500	3.7	≤6.5	22	40		≤75	1C	2C	2.75
34	453048-600	600	3.7	4.5	30	48	12.5	≤80	1C	2C	2.75
35	683033-600	600	3.7	6.5	30	33	12.0	≤91	1C	2C	2.75
36	752535-600	600	3.7	7.8	25	35	11.5	≤84	1C	2C	2.75
37	902530-600	600	3.7	8.8	25	30	12.5	≤166	1C	2C	2.75
38	751557-650	650	3.7	7.5	15	57	12.0	≤40	1C	2C	2.75
39	803623-660	660	3.7	≤8.0	36	23		≤70	1C	2C	2.75

40	503046-700	700	3.7	5.2	30	46	14.0	≤80	1C	2C	2.75
41	902535-700	700	3.7	8.8	25	35	13.0	≤20	1C	2C	2.75
42	803033-730	730	3.7	7.6	30	33	14.0	≤90	1C	2C	2.75
43	752440-740	740	3.7	7.2	24	40	13.5	≤78	1C	2C	2.75
44	552456-750	750	3.7	≤5.7	24	56		≤55	1C	2C	2.75
45	781855-750	750	3.7	8	18	55	14.0	≤55	1C	2C	2.75
46	902732-750	750	3.7	9	27	32	14.0	≤87	1C	2C	2.75
47	553442-780	780	3.7	5.6	34	42	16.0	≤68	1C	2C	2.75
48	503448-800	800	3.7	5.2	34	48	16.0	≤70	1C	2C	2.75
49	552072-800	800	3.7	≤5.5	20	72		≤40	1C	2C	2.75
50	583048-800	800	3.7	≤5.8	30	48	16.0	≤80	1C	2C	2.75
51	503450-850	850	3.7	5.0	34	50	16.5	≤60	1C	2C	2.75
52	603048-850	850	3.7	5.6	30	48	16.0	≤50	1C	2C	2.75
53	384256-900	900	3.7	≤4.0	42	56		≤60	1C	2C	2.75
54	653046-900	900	3.7	6.5	30	46	17.0	≤60	1C	2C	2.75
55	823038-900	900	3.7	8.6	30	38	18.0	≤75	1C	2C	2.75
56	103228-1000	1000	3.7	≤10.5	32	28		≤95	1C	2C	2.75
57	305069-1000	1000	3.7	3.0	50	69	20.0	≤50	1C	2C	2.75
58	553055-1000	1000	3.7	6.2	30	55	20.0	≤60	1C	2C	2.75
59	603450-1000	1000	3.7	6.0	34	50	20.0	≤60	1C	2C	2.75
60	703048-1000	1000	3.7	7.2	30	48	20.0	≤60	1C	2C	2.75
61	703448-1000	1000	3.7	≤7.0	34	48		≤50	1C	2C	2.75
62	752080-1000	1000	3.7	6.8	20	80	20.0	≤34	1C	2C	2.75
63	753048-1100	1100	3.7	7.0	30	48	20.0	≤30	1C	2C	2.75
64	503562-1100	1100	3.7	4.6	35	62	22.0	≤46	1C	2C	2.75
65	753048-1100	1100	3.7	7.0	30	48	20.0	≤55	1C	2C	2.75
66	5023104-1200	1200	3.7	5.2	23	104	24.0	≤55	1C	2C	2.75
67	633650-1200	1200	3.7	5.9	36	50	21.0	≤50	1C	2C	2.75
68	703255-1200	1200	3.7	7.0	32	55	24.0	≤55	1C	2C	2.75
69	703450-1200	1200	3.7	≤7.0	34	50		≤40	1C	2C	2.75
70	722562-1200	1200	3.7	≤7.3	25	62		≤30	1C	2C	2.75
71	304782-1300	1300	3.7	≤3.5	47	82	25.0	≤40	1C	2C	2.75
72	603562-1300	1300	3.7	6.2	35	62	26.0	≤40	1C	2C	2.75
73	903046-1300	1300	3.7	≤9.2	30	46		≤45	1C	2C	2.75
74	355069-1350	1350	3.7	≤3.7	50	69	26.0	≤40	1C	2C	2.75
75	683945-1400	1400	3.7	6.8	39	44	24.0	≤25	1C	2C	2.75
76	584448-1400	1400	3.7	≤5.8	44	48		≤55	1C	2C	3.75
77	753650-1400	1400	3.7	7.7	36	50	26.0	≤50	1C	2C	2.75
78	804044-1400	1400	3.7	8	40	44	26.0	≤55	1C	2C	2.75
79	953048-1420	1420	3.7	10.5	30	48	26.0	≤50	1C	2C	2.75
80	423885-1450	1450	3.7	4.2	38	85	28.0	≤40	1C	2C	2.75
81	6020120-1450	1450	3.7	5.6	20	120	29.0	≤30	1C	2C	2.75
82	603080-1500	1500	3.7	5.5	30	80	28.0	≤30	1C	2C	2.75
83	853448-1500	1500	3.7	8.5	34	48	26.0	≤27	1C	2C	2.75
84	103048-1500	1500	3.7	9.8	30	49	28.0	≤55	1C	2C	2.75
85	583273-1500	1500	3.7	5.8	32	73	28.0	≤41	1C	2C	2.75
86	903448-1500	1500	3.7	≤9.5	34	48		≤45	1C	2C	2.75
87	952362-1500	1500	3.7	10.0	23	62	27.0	≤50	1C	2C	2.75
88	703562-1600	1600	3.7	7	35	62	30.0	≤50	1C	2C	2.75
89	624258-1650	1650	3.7	6.0	42	58	30.0	≤28	1C	2C	2.75
90	953450-1700	1700	3.7	9.5	34	50	32.0	≤50	1C	2C	2.75

91	103746-1750	1750	3.7	≤10	37	46	31.0	≤60	1C	2C	2.75
92	103450-1800	1800	3.7	10.2	34	50	32.0	≤40	1C	2C	2.75
93	404884-1800	1800	3.7	4.2	48	84	35.0	≤40	1C	2C	2.75
94	4528135-1800	1800	3.7	≤4.5	28	135	36.0	≤40	1C	2C	2.75
95	505468-1800	1800	3.7	≤5.0	54	68		≤35	1C	2C	2.75
96	753758-1800	1800	3.7	7.5	37	59	33.0	≤42	1C	2C	2.75
97	4045100-2000	2000	3.7	4.0	45	100	39.0	≤25	1C	2C	2.75
98	623296-2000	2000	3.7	6	32	96	38.0	≤33	1C	2C	2.75
99	704460-2000	2000	3.7	6.7	44	60	37.0	≤20	1C	2C	2.75
100	455095-2000	2000	3.7	4.5	50	95	40.0	≤40	1C	2C	2.75
101	555069-2000	2000	3.7	5.2	50	69	36.0	≤50	1C	2C	2.75
102	605559-2000	2000	3.7	5.5	55	60	38.0	≤45	1C	2C	2.75
103	623296-2000	2000	3.7	≤6.2	32	96		≤30	1C	2C	2.75
104	683090-2000	2000	3.7	7	30	90	37.0	≤36	1C	2C	2.75
105	853562-2000	2000	3.7	8.3	35	62	36.0	≤45	1C	2C	2.75
106	504884-2100	2100	3.7	≤5	48	84		≤25	1C	2C	2.75
107	703090-2200	2200	3.7	≤7.2	30	90		≤22	1C	2C	2.75
108	853080-2200	2200	3.7	8.3	30	80	41.0	≤15	1C	2C	2.75
109	5528135-2200	2200	3.7	5.4	29	135	42.0	≤40	1C	2C	2.75
110	953562-2200	2200	3.7	≤9.5	35	62		≤40	1C	2C	2.75
111	455690-2300	2300	3.7	4.2	56	90	44.0	≤35	1C	2C	2.75
112	705060-2400	2400	3.7	7	50	60	44.0	≤18	1C	2C	2.75
113	683885-2400	2400	3.7	6.5	38	85	44.0	≤30	1C	2C	2.75
114	554884-2500	2500	3.7	5.5	48	84	46.0	≤25	1C	2C	2.75
115	655069-2500	2500	3.7	6.5	50	69	46.0	≤14	1C	2C	2.75
116	704865-2500	2500	3.7	7	48	65	45.0	≤12	1C	2C	2.75
117	554884-2500	2500	3.7	5.5	48	84	46.0	≤25	1C	2C	2.75
118	654284-2500	2500	3.7	≤6.5	42	84		≤40	1C	2C	2.75
119	655069-2500	2500	3.7	6.5	50	69	46.0	≤14	1C	2C	2.75
120	5045100-2600	2600	3.7	5	45	100	48.0	≤15	1C	2C	2.75
121	823090-2600	2600	3.7	8.2	30	90	47.0	≤18	1C	2C	2.75
122	805060-2700	2700	3.7	8.0	50	60	49.0	≤20	1C	2C	2.75
123	506084-2700	2700	3.7	≤5.2	60	84		≤30	1C	2C	2.75
124	854566-2800	2800	3.7	8	45	66	50.0	≤16	1C	2C	2.75
125	4048135-3000	3000	3.7	4.0	48	135	57.0	≤15	1C	2C	2.75
126	505095-3000	3000	3.7	≤5.0	50	95		≤30	1C	2C	2.75
127	654884-3000	3000	3.7	6.6	48	84	55.0	≤16	1C	2C	2.75
128	6834125-3000	3000	3.7	6.8	34	125	57.0	≤15	1C	2C	2.75
129	6834125-3000	3000	3.7	≤7.0	34	125		≤25	1C	2C	2.75
130	505690-3100	3100	3.7	5.2	56	90	57.0	≤12	1C	2C	2.75
131	505690-3100	3100	3.7	≤5.2	56	90		≤30	1C	2C	2.75
132	605585-3200	3200	3.7	6.0	55	85	60.0	≤12	1C	2C	2.75
133	555690-3200	3200	3.7	5.5	56	90	60.0	≤30	1C	2C	2.75
134	854284-3200	3200	3.7	8.5	42	84	27.0	≤24	1C	2C	2.75
135	505497-3300	3300	3.7	5.5	54	94	61.0	≤14	1C	2C	2.75
136	6045100-3300	3300	3.7	6.0	45	100	60.0	≤16	1C	2C	2.75
137	804285-3300	3300	3.7	7.6	42	85	60.0	≤12	1C	2C	2.75
138	4867102-3400	3400	3.7	4.5	67	102	64.0	≤14	1C	2C	2.75
139	704295-3400	3400	3.7	7.0	42	95	61.0	≤12	1C	2C	2.75
140	526388-3500	3500	3.7	5.2	63	88	65.0	≤13	3C	5C	2.75
141	5543128-3600	3600	3.7	5.5	43	128	65.0	≤14	1C	2C	2.75

142	7045100-3600	3600	3.7	6.8	45	100	67.0	≤15	1C	2C	2.75
143	804884-3900	3900	3.7	7.8	48	84	68.0	≤9	1C	2C	2.75
144	6443128-4000	4000	3.7	6	43	128	73.0	≤10	1C	2C	2.75
145	705585-4000	4000	3.7	7.2	55	85	72.0	≤12	1C	2C	2.75
146	824884-4000	4000	3.7	8.5	48	84	73.0	≤13	1C	2C	2.75
147	5567102-4100	4100	3.7	4.8	66	102	73.0	≤8	1C	2C	2.75
148	5548135-4300	4300	3.7	5.5	48	135	78.0	≤11	1C	2C	2.75
149	805095-4500	4500	3.7	7.8	50	95	81.0	≤10	1C	2C	2.75
150	104884-5000	5000	3.7	10	48	84	86.0	≤8	1C	2C	2.75
151	6848135-5000	5000	3.7	6.5	48	135	88.0	≤10	1C	2C	2.75
152	7543128-5000	5000	3.7	7.7	43	128	94.0	≤12	1C	2C	2.75
153	806580-5000	5000	3.7	8.5	65	80	92.0	≤10	1C	2C	2.75
154	5074135-6000	6000	3.7	≤5.2	74	135	135.0	≤15	1C	2C	2.75
155	6272145-7500	7500	3.7	6.2	72	145	139.0	≤6	1C	2C	2.75
156	8574135-10000	10000	3.7	8.7	74	135	136.0	≤4	1C	2C	2.75
157	1074135-11500	11500	3.7	9.6	74	135	210.0	≤4	1C	2C	2.75
158	301545MP-150	150	3.7	≤3.2	15	45	3.5	≤80	5C	10C	2.75
159	901723MP-230	230	3.7	≤8.5	17.5	23.5	5	≤95	5C	10C	2.75
160	8034106MP-3000	3000	3.7	≤8.0	34	106	58	≤6	5C	10C	2.75
161	4674135MP-5000	5000	3.7	≤5.0	74	135	92	≤5	5C	10C	2.75
162	8045135MP-5200	5200	3.7	≤8.0	45	135	100	≤5	5C	10C	2.75
163	9245135MP-6000	6000	3.7	≤9.2	45	135	120	≤5	5C	10C	2.75
164	683496P-2000	2000	3.7	6.8	34	96	46.0	≤7	15C	30C	2.75
165	684570P-2000	2000	3.7	≤6.9	45	70	46.0	≤8	15C	30C	2.75
166	804269P-2000	2000	3.7	7.8	42	70	46.0	≤12	15C	30C	2.75
167	902875XP-1500	1500	3.7	8.3	28	75	36	≤5	35C	70C	2.75
168	803496XP-2200	2200	3.7	8.0	34	96	55	≤4	35C	70C	2.75
169	5244130XP-2500	2500	3.7	5.2	44	130	63	≤4	35C	70C	2.75
170	5643128XP-2600	2600	3.7	5.9	43	128	69	≤3	35C	70C	2.75
171	8534106XP-2600	2600	3.7	8.2	34	106	64	≤4	35C	70C	2.75
172	7043128XP-3200	3200	3.7	6.8	43	128	80	≤3	35C	70C	2.75
173	7243128XP-3200	3200	3.7	≤7.2	43	128	65	≤2.5	35C	70C	2.75
174	8843128XP-4400	4400	3.7	8.8	43	128	110	≤3	35C	70C	2.75
175	9048135XP-5000	5000	3.7	9.0	48	135	122	≤3	35C	70C	2.75